



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 09-5003-0  
**Issue Date:** 06/06/18

**Version Number:** 12.02  
**Supersedes Date:** 01/18/18

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Windo-Weld™ Super Fast Urethane, PN 08609

#### Product Identification Numbers

ID Number	UPC	ID Number	UPC
60-9800-3692-9	00-51135-08609-4		

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive, Adhesive/Sealant for Windshields

#### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Automotive Aftermarket  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.  
Skin Corrosion/Irritation: Category 2.  
Respiratory Sensitizer: Category 1.  
Skin Sensitizer: Category 1.  
Reproductive Toxicity: Category 1B.  
Carcinogenicity: Category 2.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

**Signal word**

Danger

**Symbols**

Health Hazard |

**Pictograms****Hazard Statements**

Causes serious eye irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:

nervous system |

sensory organs |

**Precautionary Statements****Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Get medical advice/attention if you feel unwell.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

42% of the mixture consists of ingredients of unknown acute dermal toxicity.

97% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Urethane Polymer	68130-40-5	30 - 60 Trade Secret *
Carbon Black	1333-86-4	10 - 30 Trade Secret *
Sulfonic Acids, C10-18-Alkane, Ph Esters	70775-94-9	10 - 30 Trade Secret *
Kaolin, Calcined	92704-41-1	10 - 20 Trade Secret *
Hydrotreated Light Petroleum Distillates	64742-47-8	1 - 5 Trade Secret *
Toluene	108-88-3	1 - 5 Trade Secret *
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	0.1 - 1 Trade Secret *
Dibutyltin Dichloride	683-18-1	0.04 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

##### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

##### Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

##### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

DO NOT USE WATER

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

##### Substance

Carbon monoxide

Carbon dioxide

##### Condition

During Combustion

During Combustion



**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Vacuum or sweep up. **WARNING!** A motor could be an ignition source and cause flammable gases or vapors or dust in the spill area to burn or explode. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	OSHA	CEIL:0.2 mg/m <sup>3</sup> (0.02 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	

Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m3	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
TIN, ORGANIC COMPOUNDS	683-18-1	ACGIH	TWA(as Sn):0.1 mg/m3;STEL(as Sn):0.2 mg/m3	SKIN, A4: Not class. as human carcin
TIN, ORGANIC COMPOUNDS	683-18-1	OSHA	TWA(as Sn):0.1 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties



**9.1. Information on basic physical and chemical properties**

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	Neutral odor Black color
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>No Data Available</i>
Boiling Point	110 °C
Flash Point	No flash point
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	1.2 % volume
Flammable Limits(UEL)	7.1 % volume
Vapor Pressure	29 mbar [ <i>Ref Std: AIR=1</i> ]
Vapor Density	3.14 [ <i>Ref Std: AIR=1</i> ]
Density	1.205 g/cm <sup>3</sup>
Specific Gravity	1.2 [ <i>Ref Std: WATER=1</i> ]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	450 °C
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Hazardous Air Pollutants	0.0590 lb HAPS/lb solids [ <i>Test Method: Calculated</i> ]
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	70 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
Percent volatile	5.8 % weight
VOC Less H <sub>2</sub> O & Exempt Solvents	70 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]

**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat

High shear and high temperature conditions

Sparks and/or flames

Temperatures above the boiling point

**10.5. Incompatible materials**

Amines

Alcohols

Water

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

**Accelerators**

Al or Mg powder and high/shear temperature conditions

Alkali and alkaline earth metals

Reactive metals

Reducing agents

Strong acids

Strong bases

Strong oxidizing agents

Combustibles

Finely divided active metals

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

**Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

##### Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

##### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

##### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

##### Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

##### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

##### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE <sub>20</sub> - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE <sub>2,000</sub> - 5,000 mg/kg
Urethane Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Urethane Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Sulfonic Acids, C10-18-Alkane, Ph Esters	Dermal	Rat	LD50 > 1,000 mg/kg
Sulfonic Acids, C10-18-Alkane, Ph Esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Kaolin, Calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, Calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
P,P'-Methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg



ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Carbon Black	Rabbit	No significant irritation
Toluene	Rabbit	Irritant
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
P,P'-Methylenebis(phenyl isocyanate)	official classification	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Carbon Black	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
P,P'-Methylenebis(phenyl isocyanate)	official classification	Severe irritant

**Skin Sensitization**

Name	Species	Value
Toluene	Guinea pig	Not classified
Hydrotreated Light Petroleum Distillates	Guinea pig	Not classified
P,P'-Methylenebis(phenyl isocyanate)	official classification	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	Human	Sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
P,P'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
--------------------------------------	------------	-----	--

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not	20 days

Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

**Aspiration Hazard**

Name	Value
Toluene	Aspiration hazard
Hydrotreated Light Petroleum Distillates	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.



**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Not applicable

**Health Hazards**

Carcinogenicity

Reproductive toxicity

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Toluene	108-88-3	Trade Secret 1 - 5

**15.2. State Regulations**

Contact 3M for more information.

**California Proposition 65**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
Toluene	108-88-3	Developmental Toxin
Carbon Black	1333-86-4	Carcinogen

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**SECTION 16: Other information**

**NFPA Hazard Classification**

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	09-5003-0	<b>Version Number:</b>	12.02
<b>Issue Date:</b>	06/06/18	<b>Supersedes Date:</b>	01/18/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**